


DESCRIPTION: TAPERED SEAL		UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP CORNERS TOLERANCES: 1 PLACE DECIMAL $\pm .060^\circ$ 2 PLACE DECIMAL $\pm .020^\circ$ 3 PLACE DECIMAL $\pm .005^\circ$ ANGULAR DIMS $\pm 0^\circ 30'$			CINCINNATI TEST SYSTEMS 10100 PROGRESS WAY HARRISON, OH 45030	
MATERIAL: .			SolidWorks	INDICATES 500 MAXIMUM FINISH REQ'D ON SURFACES WITHOUT A SYMBOL		CUSTOMER:
FINISH: .		DRILLED AND COUNTERBORED HOLE DIAMETERS: $\pm .005^\circ / + .015^\circ$ DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5-2009		TITLE:		
HEAT TREAT: .		DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5-2009		DRAWN BY:		
				SIZE: D DATE: DWG NO.: CTS-11C-T		
				CHECKED BY: SCALE: 8:1 SHEET 1 OF 1		