



| | | | | | |
|------------------------------|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------|--|
| DESCRIPTION: Seal CTS-19B-T | | UNLESS OTHERWISE SPECIFIED | | CINCINNATI TEST SYSTEMS, INC. | |
| MATERIAL: Urethane (72 Duro) | | 1) BREAK ALL SHARP CORNERS | | 5555 DRY FORK RD., CLEVELAND, OH 43002 | |
| FINISH: | | 2) TOLERANCES: 1 PLACE DECIMAL $\pm .01$ (0.3mm) 2 PLACE DECIMAL $\pm .02$ (0.03mm) 3 PLACE DECIMAL $\pm .005$ (0.015mm) ANGULAR DIMS $\pm 0^\circ 30'$ | | DRAWN BY: [Signature] | |
| QUANTITY: | | 3) <input checked="" type="checkbox"/> INDICATES 125 | | DATE: [Blank] | |
| HEAT TREAT: | | 4) DRILLED AND COUNTERBORED HOLE DIAMETERS: $-.005 / +.015$ (-0.13mm / +0.4mm) | | PART NO: CTS-19B-T | |
| | | | | SCALE: 3:1 | |
| | | | | SHEET: [Blank] | |